

By Speed Post/FAX

**PRASAR BHARTI (BCI)
DIRECTORATE GENERAL: DOORDARSHAN
DOORDARSHAN BHAVAN, COPERNICUS MARG,
NEW DELHI – 110 001.**

F. No 1 (3) 2008-09-EI-P (TV)

Dt. 04.05.2009

To.

M/s -----

Subject: Procurement of 500W (1+1) Auto Mode VHF and UHF LPTs.

Dear Sir,

The following enclosed Clarifications to the specification no. DD/Tx/500W LPT (1+1)E-V/2008 dt.26.02.2009 are here by authorized.

This is however without any commitment whatsoever at this stage.

Yours faithfully



Preminder Singh
(Assistant Engineer)
For Director General
Tele/ Fax 23387620

E-mail: - ddpurchase401@yahoo.co.in

Copy for kind information
DE(RS)

Para No	DD specification and Clarification required	comments
4.1 (Annexure-1)	<p>Desk Top Computer system (IBM/HP/COMPAQ/Acer/Dell) Intel Pentium core 2 Duo Processor, Min 2.8 GHz, with Intel Chipset, 1 GB DDR II RAM/ 320 GB SATA HDD/ DVD Combo Drive, 17" TFT Color Monitor, Integrated Intel Graphics Media Accelerator Integrated Intel Audio with premier Internal Speakers, Integrated Gigabit Ethernet, 8 USB 2.0, 1 standard Serial, Parallel, PS2,1 RJ45,1 VGA, audio in/out, 104 keys keyboard and two button scroll optical mouse, 56.6 kbps dial up Modem, Windows XP professional OS, Anti Virus. With 800 VA Offline UPS with 30 minutes backup. <i>UPS with 30 mts backup is available with 1 KVA and above rating. It may be confirmed whether UPS of 800VA with 20 mts backup or 1KVA with 30 mts backup would be acceptable?</i></p>	<p><i>UPS of 800VA with 30 mts backup or 1KVA with 30 mts backup is acceptable</i></p>
Para 3.8 (Annexure-1)	<p>1 5/8" EIA flange (female) to N (male) connector (Reducer). <i>It is not clear why 1 5/8" female to N male is required. It would depend on the connector at the cable feeder end which is expected to be 1 5/8" male.</i></p>	<p>As the cable end is male which is fixed into EIA flange female. It is required. And any other item (adapter) is required for the completeness of the system is to be quoted by the bidder</p>

Qsh

S. Vaidyanathan
 S. Vaidyanathan
 Dy. Director (IT)